

SAFETY DATA SHEET

ULTRA 2 n 1

Section 1. Chemical Product and Company Information

Product Name : Ultra 2n1
Other means of identification : Corrosive liquid, acidic, inorganic, n.o.s., (sulfuric acid, cupric sulfate, formaldehyde)

Recommended Use : Industrial Use
Restrictions on Use : Reserved for industrial and professional use.

Supplier Information : AgroChem, Inc.
3 Duplainville Road
Saratoga Springs, NY 12866
(518) 226-4850

Code :
Date of issue : 5/1/15
EPA Registration No. Not applicable

EMERGENCY HEALTH INFORMATION : 1-866-443-9466
Outside United States and Canada CALL:

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 4), H227

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 3), H311

Skin corrosion (Category 1B), H314

Serious eye damage (Category 1), H318

Skin sensitization (Category 1), H317

Carcinogenicity (Category 1A), H350

Specific target organ toxicity - single exposure (Category 1), H370

Acute aquatic toxicity (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements,



Pictogram

Signal word Danger

SAFETY DATA SHEET

ULTRA 2 n 1

Hazard statement(s)

H227 Combustible liquid.
H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H350 May cause cancer.
H370 Causes damage to organs.
H402 Harmful to aquatic life.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P281 Use personal protective equipment as required.
P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS – none

Section 3. Composition / Information on Ingredients

Hazardous Components (Specific Chemical	OSHA PEL	ACGIH TLV	CAS #	%
---	----------	-----------	-------	---

SAFETY DATA SHEET

ULTRA 2 n 1

Identity; Common Name(s)					(optional) >= 30
Formaldehyde 50-00-0	0.75 ppm TWA PEL; 2 ppm STEL; 0.5 ppm TWA action level; Irritant and potential cancer hazard (29 CFR 1910.1048)	0.3 ppm Ceiling sensitizer	50-00-0		
Copper Sulfate 7758-99-8	1.0mg/m3 (as copper dust/mist)	1.0mg/m3 (as copper dust/mist)	7758-99-8		
Methanol 67-56-1	200 ppm TWA; 260 mg/m3 TWA	200 ppm TWA skin- potential for cutaneous absorption	67-56-1		>= 10
Sulfuric Acid Water			7732-18-5		

Section 4. First Aid Measures

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during Transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

SAFETY DATA SHEET

ULTRA 2 n 1

Use water spray to cool unopened containers.

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OS HA Regulatory Exposure limit(s):

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Formaldehyde	50-00-0	C 0.300000 ppm		

Remarks Upper Respiratory Tract irritation
 Eye irritation
 Suspected human carcinogen
 Sensitizer
 TWA 0.016000 ppm
 USA. NIOSH Recommended

SAFETY DATA SHEET

ULTRA 2 n 1

Exposure Limits
Potential Occupational Carcinogen
15 minute ceiling value
Substance listed; for more information see OSHA document
1910.1048
Substance listed; for more information see OSHA document
1910.1048
PEL 0.750000 ppm
OSHA Specifically Regulated
Chemicals/Carcinogens
1910.1048
This standard applies to all occupational exposures to formaldehyde,
i.e. from formaldehyde gas, its solutions, and materials that release
formaldehyde
OSHA specifically regulated carcinogen
STEL 2.000000 ppm
OSHA Specifically Regulated

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Face shield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to

SAFETY DATA SHEET

ULTRA 2 n 1

the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Section 9 - Physical/Chemical Characteristics

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: Blue

b) Odor pungent

c) Odor Threshold No data available

d) pH No data available

e) Melting point/freezing point No data available

f) Initial boiling point and boiling range 100 °C (212 °F)

g) Flash point 64 °C (147 °F) - closed cup

h) Evaporation rate

i) Flammability (solid, gas) No data available

j) Upper/lower flammability or explosive limits

Upper explosion limit:

Lower explosion limit:

k) Vapor pressure

l) Vapor density

m) Relative density n) Water solubility completely soluble

o) Partition coefficient:

p) Auto-ignition temperature No data available

q) Decomposition temperature No data available

r) Viscosity No data available

s) Explosive properties No data available

t) Oxidizing properties No data available

9.2 Other safety information

Relative vapor density 1.04 - (Air = 1.0)

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

Contains the following stabilizer(s):

Methanol (>=10 - <15 %)

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

SAFETY DATA SHEET

ULTRA 2 n 1

Strong oxidizing agents, Aniline, Phenol, Isocyanates, Acid anhydrides, Strong acids, Strong bases, Amines, Peroxides, Acid chlorides, Alkali metals, Reducing agents

10.6 Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: 1 - Group 1: Carcinogenic to humans (Formaldehyde)

NTP: Known to be human carcinogen (Formaldehyde)

OSHA: OSHA specifically regulated carcinogen (Formaldehyde)

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Warning: contains methanol. May be fatal or cause blindness if swallowed. Cannot be made nonpoisonous.

Liver - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence (Formaldehyde)

Stomach - Irregularities - Based on Human Evidence (Methanol)

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

SAFETY DATA SHEET

ULTRA 2 n 1

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Harmful to aquatic life.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal

service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

Section 14. TRANSPORT INFORMATION

DOT (US)

UN number: 3264 Class: 8 Packing group: III

Proper shipping name: Corrosive, Liquid, Acidic, Inorganic, n.o.s., (sulfuric acid, cupric sulfate, formaldehyde)

Description of goods: Ultra 2n1

Reportable Quantity (RQ): 125 lbs

Section 15

15. REGULATORY INFORMATION

SARA 302 Components

The following components are subject to reporting levels established by SARA Title III, Section 302:

Formaldehyde CAS-No. 50-00-0 Revision Date 2007-07-01

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Formaldehyde CAS-No. 50-00-0 Revision Date 2007-07-01

Methanol 67-56-1 2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Formaldehyde CAS-No. 50-00-0 Revision Date 2007-07-01

Methanol 67-56-1 2007-07-01

Pennsylvania Right To Know Components

Water CAS-No. 7732-18-5

Revision Date

Formaldehyde 50-00-0 2007-07-01

Methanol 67-56-1 2007-07-01

New Jersey Right To Know Components

Water CAS-No. 7732-18-5

Revision Date

Formaldehyde 50-00-0 2007-07-01

SAFETY DATA SHEET

ULTRA 2 n 1

Methanol 67-56-1 2007-07-01

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

Formaldehyde CAS-No. 50-00-0 Revision Date 2007-09-28

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Methanol

Section.16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox. Acute toxicity

Aquatic Acute aquatic toxicity

Carc. Carcinogenicity

Eye Dam. Serious eye damage

Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapor.

H227 Combustible liquid.

H301 Toxic if swallowed.

H301 + H311 +

H331

Toxic if swallowed, in contact with skin or if inhaled

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H350 May cause cancer.

H351 Suspected of causing cancer.

H370 Causes damage to organs.

H402 Harmful to aquatic life.

Skin Corr. Skin corrosion

Skin Sens. Skin sensitization

STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 1

Chronic Health Hazard: *

Flammability: 1

Physical Hazard 0

NFPA Rating

Health hazard: 1

Fire Hazard: 1

Reactivity Hazard: 0

Further information

SAFETY NOTICE:

Information contained in this material safety data sheet is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed no warranty of any kind is made with respect thereto. This information is not intended as a license to

SAFETY DATA SHEET

ULTRA 2 n 1

operate under or a recommendation to practice or infringe any patent of this Company or others covering any process, composition of matter or use. Since the Company shall have no control of the use of the product described herein, the company assumes no liability for loss or damage incurred from the proper or improper use of such product.

Emergency telephone number:

Europe: +44 (0)151 334 2774

USA: Chemtrec: (800) 424 9300

Each MSDS must be reviewed for correctness and completeness every three years.

Reviewed by _____ Reviewed by _____

Revision date _____ Revision date _____